



Car Cleaner DR-180

Version 1.0

PRODUCT DESCRIPTION

■ Outline

Car Cleaner is formulated to remove grease, oil, wax and other contaminants from bare metal, plastics, existing finishes, etc.

■ Suitable Substrates

Bare metal substrates to prepare for primer
Cured lacquer or acrylic urethane finishes to prepare for finishing
Removes a sanding residue before recoating

■ Application

Read specific TDS for proper application.
Car Cleaner may be prohibited from using in VOCs regulated areas. Always check local regulations.

■ Cleaning Technique

When a repair is to be made or a finish is to be recoated, the first thing to do after washing the car is to clean and degrease the body panel under treatment. Thereafter, immediately wipe off the surface with clean and dry cloth. Always use two cloths because one cloth might cause difficulties in removing and greasing dirt.

■ Under Existing Finishes

1. Wash down the vehicle with detergent and warm water. This will dissolve water-soluble contaminants.
2. Wash down the area to be repaired with Car Cleaner . This removes any contaminar which cannot be removed by water.
3. With a clean towel, wipe out Car Cleaner before it evaporates.
 - Always use one fresh towel for washing down and one fresh dry towel for wiping d
 - Replace towels regularly.



Car Cleaner DR-180

Version 1.0

■ Sanded Existing Finishes

Repeat Step 2 and 3 of 'Under Existing Finishes' one more time after sanding and prior to topcoating.

■ Plastic Parts

1. Wash down the unpainted plastic part with warm water and detergent.
2. Wash down the plastic part with Car Cleaner.
3. With a clean towel, wipe out the Car Cleaner before it evaporates.
4. When cleansing unpainted plastic parts, let them be dried off for 20 to 30 minutes after applying Car Cleaner and before applying a primer.

■ Bare Metal

1. Wash down the metal with Car Cleaner. This ensures that stubborn contaminants are to be removed during final cleaning.
2. With a clean towel, wipe out the Car Cleaner before it evaporates.
 - Always use one fresh towel for washing down and one fresh dry towel for wiping d
 - Replace towels regularly.

■ Health and Safety

1. Be well-informed of MSDS before use.
2. Follow all the directions labeled on the container.
3. For safety reasons, work in the fully-ventilated place.
4. Wear safety glasses, coveralls and latex gloves when mixing and applying.

This data sheet is based on the test results and experiential bases of NOROO but might vary with the actual working environment and applying condition. This data is the intellectual property of NOROO Paint thus copying and distribution without permission are strictly prohibited. For more information, please contact the technical team or refer to our homepage. (<http://www.autorefinishes.co.kr>)