

## PRODUCT DESCRIPTION

### ■ Outline

Blending Solvent DR-600 is a ready-to-spray blending agent used to melt the edge of NOROO® 2K urethane topcoats. It is specifically designed as an edge blending solvent for invisible blend repairs where full panel repairs are not desirable. It is designed for use in the following NOROO urethane topcoat systems.

DR-600 is a fast dry, ready-to-spray blending agent. It improves blending of NOROO® single stage colors and clearcoats.

### ■ Product Configuration

Product Name	Pack(ℓ)	Contents(ℓ)	Storage
Blending Solvent DR-600	4.0	4.0	24 months

\* Standard temperature of storage is 20°C.

## APPLICATION GUIDE

### ■ Use

#### Stirring



Stir Blending Solvent DR-600 thoroughly before use. DR-600 is packaged ready to spray.

#### Spray Condition



1.5~2.0 bar (gravity feed)  
1~2 wet coats keeping 15~20cm from the surface  
Fluid tip : 1.2~1.5mm, D.F.T.=5~10 $\mu$ m



2.0~2.5 bar (siphon feed)  
1~2 wet coats keeping 15~20cm from the surface  
Fluid tip : 1.4~1.6mm, D.F.T.=5~10 $\mu$ m

#### Protective Equipment



Use fresh air mask or charcoal respirator to avoid inhaling or being exposed to fumes.

## ADDITIONAL INFORMATION

### ■ VOC Content

VOC content of 800g/liter

### ■ Health and Safety

1. Be well-informed of MSDS before use.
2. Follow all the directions labeled on the container.
3. For safety reasons, work in the fully-ventilated place.
4. Wear safety glasses, coveralls and latex gloves when mixing and applying.

This data sheet is based on the test results and experiential bases of NOROO but might vary with the actual working environment and applying condition. This data is the intellectual property of NOROO Paint thus copying and distribution without permission are strictly prohibited. For more information, please contact the technical team or refer to our homepage. (<http://www.autorefinishes.co.kr>)